

## 60X60X25 mm

## JF0625-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Amp)	Noise (dBA)	Weight (g)
JF0625B1TRAL	B	12	10.2 ~ 13.8	35.70	0.509	7200	0.38	4.56	0.38	46.9	59
JF0625B1TR	B			29.77	0.401	6000	0.37	4.44	0.38	42.1	
JF0625-1UR	B, H			27.17	0.338	5500	0.29	3.48	0.30	40.1	
JF0625-1S	B, H, S			24.12	0.263	5000	0.22	2.64	0.22	37.2	
JF0625-1H	B, H, S			21.56	0.215	4500	0.20	2.40	0.23	34.5	
JF0625-1M	B, H, S			19.15	0.172	4000	0.16	1.92	0.20	30.5	
JF0625-1L	B, H, S			16.78	0.134	3500	0.13	1.56	0.17	27.4	
JF0625-1E	B, H, S			14.26	0.097	3000	0.11	1.32	0.11	23.1	
JF0625-1V	B, H, S			11.84	0.070	2500	0.08	0.96	0.08	20.1	
JF0625B2TRAJ	B	24	20.4 ~ 27.6	34.71	0.491	7000	0.21	5.04	0.21	46.1	
JF0625B2TR	B			29.77	0.401	6000	0.20	4.80	0.21	42.1	
JF0625-2UR	B, H			27.17	0.338	5500	0.16	3.84	0.16	40.1	
JF0625-2S	B, H, S			24.12	0.263	5000	0.13	3.12	0.14	37.2	
JF0625-2H	B, H, S			21.56	0.215	4500	0.12	2.88	0.17	34.5	
JF0625-2M	B, H, S			19.15	0.172	4000	0.11	2.64	0.13	30.5	
JF0625-2L	B, H, S			16.78	0.134	3500	0.10	2.40	0.12	27.4	
JF0625-2E	B, H, S			14.26	0.097	3000	0.07	1.68	0.07	23.1	
JF0625-2V	B, H, S			11.84	0.070	2500	0.06	1.44	0.06	20.1	
JF0625B4UR	B, H	48	40.8 ~ 55.2	27.17	0.338	5500	0.11	5.28	0.11	40.1	
JF0625B4SR	B, H			24.12	0.263	5000	0.09	4.32	0.09	37.2	
JF0625B4HR	B, H, S			21.56	0.215	4500	0.07	3.36	0.08	34.5	
JF0625B4MR	B, H, S			19.15	0.172	4000	0.06	2.88	0.07	30.5	
JF0625B4LR	B, H, S			16.78	0.134	3500	0.05	2.40	0.06	27.4	

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".

Please contact us for detail if your request bearing system is not shown in the above list.

